



Anti Spatter Spray

An aerosol product that protects materials and surfaces in welding area against particles spattering during welding process. It ensures a perfect welding operation.

Advantages:

- Anti-adhesion product for arc welding.
- Prevents the adhesion of "projections" on all treated surfaces.
- Suitable for protecting nozzles, weld units and tools.
- Not flammable after evaporation of solvent.

Usage Areas:

- Used in welding processes due to its ability to prevent adhesion of spattering particles to the around areas and surfaces.
- Nozzles and shrouds.
- Torches.
- Workpieces and parts.
- Jigs.
- Automatic and semi-automatic welding.
- Welding robots.

How to use:

- Shake the can vigorously before use.
- Thoroughly clean the surfaces needing treatment.
- Spray evenly over the whole area from a distance of approx. 8-10inch.

- Spray into the welding nozzle before starting and re-apply as required.

Limitations:

- Do not spray onto extremely hot brakes and clutches.
- Do not spray on a naked flame or glowing objects have become.

Safety

- Use gloves when working.
- Pressurized container. Do not expose to temperatures higher than 122°F.
- Keep away from direct sunlight
- Do not pierce or burn, even after use.
- Keep away from sources of ignition, no smoking.
- Keep out of the reach of children.

Shelf Life:

- 24 months, if stored properly.

Packaging (Weight/Volume):

- 12 oz Aerosol, 12 pcs in a box.

Physical & Chemical Properties:

- Chemical Structure: Liquid Aerosol
- Appearance: Transparent
- Specific Gravity: 8,2 lb/gal
- Odor: Characteristic
- Flash Point: N/A