

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 30.11.2021 Version: 00

SECTION 1: Identification

Identification

Product form : Mixture

Trade name KRAKEN FOAM CLEANER

Relevant identified uses of the substance or mixture and uses advised against

No additional information available

Details of the supplier of the safety data sheet

LOTUS GLOBAL TRADE LLC 8684 VIRGINIA MEADOWS DR, MANASSAS, VA, 20109 UNITED STATES OF AMERICA T + 1 571 445-5665

Emergency telephone number

For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night 1-800-424-9300

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS-US classification

Flammable aerosols, Category 1 H222 Serious eye damage/eye irritation, Category 2A H319 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

Full text of H statements : see section 16

Label elements

GHS-US labelling

Hazard pictograms (GHS-US)





GHS02

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H222 - Extremely flammable aerosol H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking Precautionary statements (GHS-US)

P211 - Do not spray on an open flame or other ignition source P251 - Pressurized container: Do not pierce or burn, even after use

P261 - Avoid breathing gas, spray, vapours P280 - Wear eye protection, face protection

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P312 - Call a doctor, a POISON CENTER if you feel unwell

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

EN (English) 30.11.2021 Page 1

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 30 11 2021 Version: 00

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixtur

Name	Product identifier	%	GHS-US classification
Ethyl acetate	(CAS No) 141-78-6	30 - 40	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Acetone, propan-2-one, propanone	(CAS No) 67-64-1	20 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Petroleum gases, liquefied, Petroleum gas	(CAS No) 68476-85-7	1 - 15	Flam. Gas 1, H220

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to First-aid measures after eye contact

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion Call a poison center or a doctor if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact Repeated exposure may cause skin dryness or cracking.

Symptoms/injuries after eye contact Eye irritation.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard Pressurised container: May burst if heated.

Reactivity Extremely flammable aerosol. Pressurised container: May burst if heated.

Advice for firefighters

Do not attempt to take action without suitable protective equipment. Self-contained breathing Protection during firefighting

apparatus. Complete protective clothing

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

611 For non-emergency personnel

Emergency procedures Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Environmental precautions

Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information Dispose of materials or solid residues at an authorized site.

30.11.2021 EN (English) 2/8

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 30.11.2021 Version: 00

Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

Conditions for safe storage, including any incompatibilities

Storage conditions

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

Control parameters

ethyl acetate (141-78-6)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Ethyl acetate	
ACGIH TWA (ppm)	400 ppm	
Remark (ACGIH)	TLV® Basis: URT & eye irr	
Regulatory reference	ACGIH 2020	
USA - OSHA - Occupational Exposure Limits		
Local name	Ethyl acetate	
OSHA PEL (TWA) (mg/m³)	1400 mg/m³	
OSHA PEL (TWA) (ppm)	400 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
acetone; propan-2-one; propanone (67-64-1)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Acetone	
ACGIH TWA (ppm)	250 ppm	
ACGIH STEL (ppm)	500 ppm	
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI	
Regulatory reference	ACGIH 2020	
USA - ACGIH - Biological Exposure Indices		
Local name	ACETONE	
Biological Exposure Indices (BEI)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns	
Regulatory reference	ACGIH 2020	
USA - OSHA - Occupational Exposure Limits		
Local name	Acetone	
OSHA PEL (TWA) (mg/m³)	2400 mg/m³	
OSHA PEL (TWA) (ppm)	1000 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
Petroleum gases, liquefied; Petroleum gas; (68476-85-7)		
USA - ACGIH - Occupational Exposure Limits		
Local name	L.P.G (Liquefied petroleum gas)	
Remark (ACGIH)	TLV® Basis: Simple Asphyxiant	
Regulatory reference	ACGIH 2020	
USA - OSHA - Occupational Exposure Limits		
Local name	L.P.G. (Liquified petroleum gas)	
OSHA PEL (TWA) (mg/m³)	1800 mg/m³	
OSHA PEL (TWA) (ppm)	1000 ppm	

EN (English) 3/8 30.11.2021

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 30.11.2021 Version: 00

Regulatory reference (US-OSHA)

OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

EN 166. Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Auto-ignition temperature

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance Liquid under pressure. Clear. Colourless. Colour Odour Characteristic No data available Odour threshold рΗ No data available No data available Melting point No data available Freezing point Boiling point No data available

Flash point : 24 °C

Relative evaporation rate (butylacetate=1) : No data available Flammability (solid, gas) : No data available Explosive limits : No data available

Explosive properties : Pressurised container: May burst if heated.

Oxidising properties : No data available
Vapour pressure : No data available
Relative density : No data available
Relative vapour density at 20 °C : No data available
Density : 0.85 g/cm³
Solubility : No data available
Log Pow : No data available

Decomposition temperature : No data available Viscosity : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available

30.11.2021 EN (English) 4/8

No data available

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 30.11.2021 Version: 00

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ethyl acetate (141-78-6)	yl acetate (141-78-6)	
LD50 dermal rabbit	> 20000 mg/kg bodyweight Animal: rabbit, Animal sex: male	
acetone; propan-2-one; propanone (67-64-1)		
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female	
LC50 inhalation rat (mg/l)	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4	

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

acetone; propan-2-one; propanone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)

STOT-single exposure : May cause drowsiness or dizziness.

ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
acetone; propan-2-one; propanone (67-64-1)	
acetone; propan-2-one; propanone (67-64-1)	

STOT-repeated exposure : Not classified

ethyl acetate (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)

Aspiration hazard : Not classified

30.11.2021 EN (English) 5/8

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 30.11.2021 Version: 00

Viscosity, kinematic : No data available

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

hyl acetate (141-78-6)	
LC50 fish 1	230 mg/l Test organisms (species): Pimephales promelas
NOEC (chronic)	2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
acetone; propan-2-one; propanone (67-64-1)	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas

2

DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

30.11.2021 EN (English) 6/8

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 30.11.2021 Version: 00

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Emergency Response Guide (ERG) Number : 126

Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : 1950
Proper Shipping Name (IMDG) : AEROSOLS
Class (IMDG) : 2 - Gases
MFAG-No : 126

Air transport

UN-No. (IATA) : 1950

Proper Shipping Name (IATA) : Aerosols, flammable

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

	ethyl acetate (141-78-6)	
	Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313	
CERCI A RO 5000 lb		

acetone; propan-2-one; propanone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 5000 lb

Petroleum gases, liquefied; Petroleum gas; (68476-85-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

ethyl acetate (141-78-6)

Listed on the Canadian DSL (Domestic Substances List)

acetone; propan-2-one; propanone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

Petroleum gases, liquefied; Petroleum gas; (68476-85-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

30.11.2021 EN (English) 7/8

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 30.11.2021 Version: 00

15.3. US State regulations

Component	State or local regulations
ethyl acetate(141-78-6)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
acetone; propan-2-one; propanone(67-64-1)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
Petroleum gases, liquefied; Petroleum gas; (68476-85-7)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 30.11.2021

Full text of H-statements:	
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

SDS US KRAKEN

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable

30.11.2021 EN (English) 8/8